

KBox C-103-CFL-x



High-End Industrial Computer Platform for Control Cabinet Applications


- ▶ Based on 8th/9th Gen Intel® Core™ or Xeon® E-2276ME for demanding control applications
- ▶ Highest system availability: Fanless up to 65 °C, Goldcap backup, redundant PSU option, recovery button
- ▶ Optimized for control and Soft-PLC applications: Fieldbus and NVRAM option
- ▶ High flexibility and expandability

► TECHNICAL INFORMATION


	KBox C-103-CFL-4	KBox C-103-CFL-2	KBox C-103-CFL-1	KBox C-103-CFL-0
PROCESSORS	8th/9th Generation Intel® processor via COM Express® type 6: - Xeon® E-2276ME: 6x 2.8 GHz, 12 MByte cache - Core™ i7-9850HE: 6x 2.7 GHz, 9 MByte cache - Core™ i5-8400H: 4x 2.5 GHz, 8 MByte cache - Core™ i3-9100HL: 4x 1.6 GHz, 6 MByte cache - Celeron® G4930E: 2x 2.4 GHz, 2 MByte cache			
PLATFORM CONTROLLER HUB	Intel® CM246 (Xeon®) or QM370			
MEMORY	Up to 64 GByte DDR4 RAM, non-ECC/ECC			
NON-VOLATILE RAM (NVRAM)	1 MByte FRAM for static values, available on project request			
RTC	High-precision RTC with gold-cap backup			
INTERFACES	4x 10/100/1000 MBit/s Ethernet with IEEE1588 support, WOL 3x USB 3.0, 3x USB 2.0 2x DisplayPort 1x RS232/RS422/RS485 8x LEDs 2x Buttons: Power/Reset & Recovery			
OPTIONAL INTERFACES	CAN module for layer 2 CAN (SJA1000) 2nd COM port RS232/RS422 3rd DisplayPort or Kontron Widelink option via adapter module 2nd 24 VDC power input, hot standby functionality			
STORAGE DRIVES	1x M.2 2280 B-Key and 1x M.2 2280 M-Key, 2x 2.5" SATA SSD/HDD internal, optional accessible via removable drive assemblies	1x M.2 2280 B-Key and 1x M.2 2280 M-Key, 2x 2.5" SATA SSD/HDD internal, optional accessible via removable drive assemblies	1x M.2 2280 B-Key and 1x M.2 2280 M-Key, 1x 2.5" SATA SSD/HDD internal, optional accessible via removable drive assembly	1x M.2 2280 B-Key and 1x M.2 2280 M-Key, 1x 2.5" SATA SSD/HDD internal
EXPANSIONS	2x PCIe x4 + 2x PCIe x1, 1x mPCIe for Fieldbus or WIFI expansion 1x M.2 2242 B-Key for LTE expansion, SIM card socket	2x PCIe x4 or 1x PCIe x8, 1x mPCIe for Fieldbus or WIFI expansion 1x M.2 2242 B-Key for LTE expansion, SIM card socket	1x PCIe x4 or 1x PCIe x8, 1x mPCIe for Fieldbus or WIFI expansion 1x M.2 2242 B-Key for LTE expansion, SIM card socket	1x mPCIe for Fieldbus or WIFI expansion 1x M.2 2242 B-Key for LTE expansion, SIM card socket
POWER SUPPLY	24 VDC (17-36 VDC), up to 20 ms hold-up			
DIMENSION (H X W X D)	290 x 195 x 210 mm (11.42" x 7.68" x 8.27")	290 x 155 x 210 mm (11.42" x 6.1" x 8.27")	290 x 130 x 210 mm (11.42" x 5.12" x 8.27")	290 x 117 x 210 mm (11.42" x 4.61" x 8.27")
MOUNTING	Control cabinet key holes, book size format			
COOLING	Fanless, optional with FAN			
ENVIRONMENTAL				
OPERATING TEMPERATURE	with Intel® Core™ i3/i5 and Celeron®: 0 °C to +65 °C (32 °F to 149 °F) with Intel® Core™ i7: 0 °C to +60 °C (32 °F to 140 °F)			
STORAGE TEMPERATURE	-40 °C to +75 °C (-40 °F to 167 °F)			
CLIMATIC HUMIDITY	93 % RH at 40 °C, non-condensing (acc. to IEC 60068-2-78)			
APPROVALS	CE, CB, UL, FCC			
SOFTWARE SUPPORT	Windows® 10, Windows® Server 2019, Linux			
SECURITY FEATURES	TPM 2.0 controller and Kontron APPROTECT security solution based on Wibu-Systems CodeMeter®			
WEIGHT	6 kg (13.22 lbs.)	4.75 kg (10.47 lbs.)	4.6 kg (10.14 lbs.)	3.8 kg (8.37 lbs.)

► DIMENSIONS - FRONT SIDE


KBox C103-CFL-4




KBox C103-CFL-2




KBox C103-CFL-1



KBox C103-CFL-0



► DIMENSIONS - RIGHT SIDE



► GLOBAL HEADQUARTERS

Kontron Europe GmbH

Gutenbergstraße 2
85737 Ismaning, Germany
Tel.: +49 821 4086-0
Fax: +49 821 4086-111
info@kontron.com

www.kontron.com